

OCOM 2d

M / N OCBS-W234



2.4GHz

80

100

190mA 40,000

12

1000

	ABS + PC + TPU
	5V±5
	190mA
	3.7V 2000mAH 18650
	6.5
	> 12
	170±5

□□□□	
□□□□	2.4GHz□
□□□□	50-80M
□□	□□LED□□+□□LED
□□	2M□□40000□□□□□□□□
□□□□	Codabar□Code11□Code39 / Code93□UPC / EAN□Code128 / EAN128□InterLeaved2of5□Matrix2of5□MSI CODE□Standard2of5□QR□□□□□□□□PDF417
□□□	Code39 5mil□QR 8.7mil□PCS45□
□□	5MIL CODE39□5--12 CM 15MIL CODE39□4--25 CM 10MIL CODE93□4--21 CM 15MIL UPC / EAN□4--25 CM 20MIL QR□4--25 CM
□□□□	400times /□
□□□	1/5□
□□□□	□□□□□□□□□□□□
□□□□	5 *5cm <sup>2</sup> - 30 *30cm <sup>2</sup>
□□□□	□□□□□□□□LED□
□□□□□	□□35□
□□□□	□□0-360°□□□±65°□□□±60°
□□□□	
IP□□	≥IP54
□□□□	0□50°C/ 32□122°F
□□□□	0□50°C/ 32□122°F
□□□□	5 - 95□□□□□□□
□□□□	5 - 95□□□□□□□
□□□□	15KV
□□□□	1.5M□□□□□□□□□□









50 O2 Equicom .....

OCOM "OEM / ODM"

·POS;

·500;

·O2 Star .....

·2600 163;

·24;

·12 OEM / ODM;

·;

·ISO 9001 FCC CE Rohs Soncap SASO POA BIS;

·MOQ;

·12 + 1;

·“”

·“”



1. 目的

2. 背景

3. 背景

2. 背景

4. 背景

3. 目的

OCOM 提供...  
500... 100...  
12 + 1... 24...  
30... DOA... DOA...  
...

4. 目的

5. 目的

5. 目的



□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□