

USB

OCBS-LA11

OCBS-LA11

OCBS-LA11	
OCBS-LA11	OCBS-LA11 650-670nm
OCBS-LA11	OCBS-LA11 100mm
OCBS-LA11	2.5~600mm 100mm UPC / EAN
OCBS-LA11	OCBS-LA11
OCBS-LA11	PCS 0.9 0.10mm 4mil
OCBS-LA11	30mm 650nm
OCBS-LA11	OCBS-LA11
OCBS-LA11	UPC / EAN UPC / EAN UCC / EAN 128 39 ASCII 39 trioptic 128 128 ASCII codabar 2 of 5 2 of 5 93 MSI 11 ATA RSS 2 of 5 ...
OCBS-LA11	
OCBS-LA11	PS2 RS232 USB
OCBS-LA11	DC + 5V +/- 5
OCBS-LA11	100
OCBS-LA11	< 40mA
OCBS-LA11	OCBS-LA11 RS232
OCBS-LA11	45° 60°
OCBS-LA11	L165mm X W63mm X H87mm
OCBS-LA11	129mm
OCBS-LA11	OCBS-LA11
OCBS-LA11	OCBS-LA11
OCBS-LA11	
OCBS-LA11	0°C 40°C
OCBS-LA11	-40°C ~ 60°C
OCBS-LA11	5~95
OCBS-LA11	+/- 15KV +/- 8KV
OCBS-LA11	1.5
OCBS-LA11	
EMI / RFI	FCC A CE
OCBS-LA11	CDRH 2

OCBS-LA11



## *Handheld Laser Barcode Scanner*

**OCBS-LA11**



**Product Picture**





## Features

***Simple but not easy***

Handheld laser barcode scanner with  
auto sense function;



Flexible operation with 360 degree



rotation metal stand;



High scan rate (100 scans/sec) and  
long reading distance;



Excellent decode capability;





KBW, RS232 and USB supported;



## ||| All-round show





## Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance:	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	30%, minimum reflective difference (@650nm)
Error Rate:	1/3000000
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...

<b>Physical Characteristics</b>	
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L 165mm X W63mm X H87mm
Weight:	129g (without stand)
Stand	Optional
Color:	Grey and black
<b>User Environment</b>	
Operating Temperature:	0°C~40°C
Storage Temperature:	-40°C~ 60°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
<b>Safe:</b>	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port



5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com),  
Together we quest for the best.

