

IOS
(OCPP-M07)

IOS

IOS 800x480 16.7M 320x240

- n Windows\Java\Linux\Android\ IOS 8.0;
- n USB \ RS232 800x480;
- n SDK\Android\ IOS CE 8.0;
- n 1 D\2D 800x480 QR 800x480;
- n 100 800x480 800x480;
- n 57 * 50 800x480
- n 800x480 800x480 (7 Android\Windows\Linux 800x480);
- n 1500mAh) 4 ~ 5 800x480;
- n 800x480 800x480 800x480
- n 90 800x480;
- n 100 800x480 800x480;
- n 800x480;
- n ESC\POS 800x480;

IOS

IOS 800x480 16.7M 320x240

IOS	105 x 75 x 45 mm
IOS	134 g
IOS	800x480
IOS	800x480
IOS	ESC\POS 800x480
IOS	48 mm
IOS	90 800x480
IOS	8 dots/mm(203dpi)
IOS	12 x 24 \ 24 x 24
IOS	32 \ 16columns
IOS	1.5 x 3.0 mm(W x H) \ 3.0x3.0mm(WxH)
IOS	58.0±0.1 mm x 40.0 mm
IOS	0.06 \ 0.08 m m
IOS	800x480 V 800x480
IOS	USB\RS-232 800x480
IOS	256 KB
IOS	9V 800x480
IOS	7.4 v DC \ 1500mAh; 800x480 4-5 800x480 800x480 120-150 mm
IOS	800x480 800x480
IOS	800x480 800x480 10% \ 90%

□□□□	□□:-20 ~ 70 □□□□□□□ 5%~95%
□□□□	□□□□□□□ □□□□□□□□□□□□□ 30 ASCII □□□
□□	□□□□□□□ □□\"1234\"□□□□□□□□□□□□□ □ □ 6 □□□
□□□□□□	3.5 * 1.1 □□
	OCPP-M07-BB □□□□USB + COM + □□□□□□
	OCPP-M07-BB-AI □□□□ + IOS□USB + COM + □□□□□□
□□□□	OCPP-M07-B □□□□USB + COM + □□□□□□□;
	OCPP-M07-U □□□□□□□□□□□□□ USB + COM□□□□□□
	OCPP-M07-BB-AA □□□□ + IOS□USB + COM + □□□□□□7 android + 1 □□ □□□□

□ □ □ □ □ □ □ □



1



1

* WIindows ████

* CD III