

OCBS-L009

OCBS-L009



200

200scan / sec

KBW

RS232

USB

650nm

200

|               |           |
|---------------|-----------|
| 650nm         | 200       |
| 200           | 32        |
| 2.5           | 50        |
| 600mm         | 60        |
| 100           | 220       |
| UPC / EAN     | 200       |
| 50            | 3mil      |
| 60            | 5mil      |
| 220           | 30        |
| 200           | UPC / EAN |
| 39            | ASCII     |
| 39            | 128       |
| 128           | 2 of 5    |
| 5 of 2        | 93        |
| MSI           | 11        |
| RSS           | 5 of 2    |
| MSI / Plessey | UCC / EAN |
| 128           | GS1       |
| RSS           |           |
| ±65°          | ±60°      |
| ±42°          |           |

|        |                            |
|--------|----------------------------|
| □□□□   |                            |
| □□□□□□ | PS2□RS232□USB              |
| □□□    | 5V DC±5□                   |
| □□□    | 85 mA□□□□; 100□□□□         |
| □□□    | □□□□LED                    |
| □□     | ABS                        |
| □□     | □□□                        |
| □□□    | 156 * 68 * 83□□□□*□*□□     |
| □□□    | 235□                       |
| □□□    | □□□□□                      |
| □□     |                            |
| □□□□□  | 0□□45□                     |
| □□□□□  | -40□□60□                   |
| □□□    | 5□-90□□□□□□                |
| □□□□□  | □□+/- 15KV□□□□□+/- 8KV□□□□ |
| □□□□   | 0□100,000□□□               |
| □□□□□  | □□□□□1.5m□□□□□□□           |
| □□□□   | EN60825-1□□□1              |



OCBS-L009





OCBS-L009





OCBS-L009





OCBS-L009





20076 OCOM ISO9001 2008 159 /  
2300 50  
02 Equicom ...



## ► Company



## ► Certificates



## ► Payment



□□□□□□□

- POS
- 500
- 102 Star ...
- 163 / 2600
- 24
- 12 OEM / ODM
- 
- ISO 9001 FCC CE Rohs Soncap SASO POA BIS
- 
- 12 + 1
- “
- “ ”



