

58

OCPP-M06



Table

Size (mm)	105×75×45mm
Resolution	134dpi
Interface	USB
Power Supply	5VDC
Operating Temperature	ESC / POS compatible
Print Speed	48mm/sec
Print Width	90mm / sec
Print Density	8dots/mm 203dpi
Print Format	12x24 / 24x24
Print Length	32 / 16
Print Area	1.5 x 3.0 inches / 3.0x3.0 inches
Print Resolution	58.0±0.1mm x 40.0mm
Print Thickness	0.06-0.08mm
Print Speed	Variable/Standard
Connectivity	USB/RS-232
Flash	256KB

電圧		9V DC / 2A
電流		7.4V DC / 1500mAh;充電時間4-5時間;充電電圧120-150mA
電圧		充電電圧
電圧		充電-10℃50℃充電10℃90℃
電圧		充電-20℃70℃充電5℃95℃
電圧		充電電圧充電電圧30℃ASCII充電
電圧		充電電圧充電電圧“ 1234”充電電圧充電電圧6℃
電圧		3.5 * 1.1℃
電圧	OCPP -M06-BB	Android充電USB + COM +充電電圧
	OCPP -M06-BB-AI	Android + IOS充電USB + COM +充電電圧
	OCPP -M06-B	Android充電USB + COM +充電電圧
	OCPP -M06-U	充電電圧Android充電USB + COM充電電圧
	OCPP -M06-BB-AA	Android + IOS充電USB + COM +充電電圧7℃android +1℃











[illegible]

□OEM / ODM□

□□□□□□□□

► Company



► Certificates



► Payment



