

# 2D Barcode

OCBS-T203

Barcode

32-bit DSP	32-bit ARM DSP; 1D; 2D
2D	
	0 - 200 @ UPC / EAN 100 PCS90
	5mil
USB	windows
	100
	72
LED	LED
	50

Barcode

CMOS	CMOS	
752 * 480 CMOS	752 * 480 CMOS	
LED	LED	
Code128 UCC / EAN-128 AIM-128 EAN-8 EAN-13 ISBN / ISSN UPC-E UPC-A Interleaved 2 of 5 ITF-6 ITF-14 Matrix 2 of 5 25 25 Code 39 Codabar Code 93 Code 11 Plessey MSI-Plessey GS1-DataBar RSS RSS-14 RSS-Limited RSS-Expand PDF417 QR QR1 / 2 ECC200 ECC000,050,080,100,140	Code128 UCC / EAN-128 AIM-128 EAN-8 EAN-13 ISBN / ISSN UPC-E UPC-A Interleaved 2 of 5 ITF-6 ITF-14 Matrix 2 of 5 25 25 Code 39 Codabar Code 93 Code 11 Plessey MSI-Plessey GS1-DataBar RSS RSS-14 RSS-Limited RSS-Expand	
	PDF417 QR QR1 / 2 ECC200 ECC000,050,080,100,140	
≥5	≥5	
2.5	2.5	
±50° @ 0° 0°	±50° @ 0° 0°	±50° @ 0° 0°
±360° @ 0° 0°	±360° @ 0° 0°	±360° @ 0° 0°
±60° @ 0° 0°	±60° @ 0° 0°	±60° @ 0° 0°
USB HID-KBW USB HID-POS TTL-232 RS-232	USB HID-KBW USB HID-POS TTL-232 RS-232	
44° 33.2°	44° 33.2°	
EAN-13 PDF 417 39 4 10	EAN-13	0-20 13mil
	PDF 417	0-7 6.67mil
	39	0-12 5 1
	4	0-4 10MIL
	10	0-10 15
L * W * H	89 * 108 * 143 2	
245	245	
20°C + 50°C -4°F 122°F	20°C + 50°C -4°F 122°F	
-40°C + 80°C -40°F 176°F	-40°C + 80°C -40°F 176°F	
5 95	5 95	
ESD	±14 ±8	
1.2	1.2	
IP 52	IP 52	



OCBS-T203





OCBS-T203





OCBS-T203

