

无线手持终端

 M / N 型OCBS-E7



- 无线
- 2.4G 16通道
- 16MB 内存
- 433MHz 无线频率
- 16通道
- 无线频率
- ABS + 无线频率

无线	
无线	OCBS -E7
无线	无线
CPU	72MHz
无线	T9
无线	16KB
无线	16MB
无线	2.4'
无线	16通道65536
无线	240 * 320
无线	无线3.7V 1900mAh
无线	16
无线	15
无线	138×60×30

	材料	ABS + 防火
	重量	100g
	尺寸	160mm
	厚度	8mm
	表面	哑光/半哑光/高光
	认证	CE/FCC DOC
	速度	650mm/s
	精度	±0.05mm
	公差	100±2mm/100mm
	厚度	300mm
	厚度	20mm @ 200mm @ 200mm
	厚度	0.25mm @ 0.33mm PCS 90mm
	厚度	30°
	厚度	65°
	厚度	55°
	厚度	30mm
	厚度	100/100mm
	厚度	1/500mm
	厚度	100mm
	厚度	EAN-8/EAN-13/UPC-A/UPC-E/Code 39/Code 93/Code 128/EAN128/Codabar/Industrial 2 of 5/Interleave 2 of 5/Matrix 2 of 5/MSI
接口	USB 2.0	
频率	433MHz	300mW
温度	-20°C	60°C
温度	0°C	45°C
速度	5mm/s	95mm/s
速度	5,000 Lux	10000 Lux







OCBS-E7







2007 6 OCOM ISO9001 2008
159 / 2300 50

02 Equicom ...

OCOM “ ” OEM / ODM

► Company



► Certificates



► Payment



□ □ □ □ □ □ □ □

- POS
- 500
- 1O2Star ...
- 163/2600
- 24
- 12OEM / ODM
-
- ISO 9001FCCCERohsSoncapSASOPOABIS
-
- 12 + 1
- “”
- “”



