

QR

OCBS-2008

Features

-
-
-
- 4mil
-
- SDK / API
-
-

Specifications

•		• LED
•		•
•		•
•		• LED
•		•
•		CMOS
•		640 * 480 256
•		13mil UPC40
•		50; 20
•		≥4mil
•	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN, EAN, Bookland, ISSN, 39, 39, ASCII, 32, Trioptic, 39, 5, 2, 5, 5, NW7, 128, UCC / EAN 128, GS1-128, ISBT 128, CODE93, 11, USD-8, MSI / Plessey
•	2D	PDF417, MicroPDF417, QR, DataMatrix, Aztec, GS1
•		39, 5mil, 50, 120 39, 10MIL, 25, 250 UPC / EAN, 13mil, 20, 320 7.5mil, 63, 150 PDF417, 6.6mil, 62, 145
•		±45° @ 0° ±30° @ 0° ±45° @ 0°
•		•
•		USB, USB COM
•		3.3V, 5V DC
•		2.0, 400
•		2.5, 450
•	DC	5.5V 1A
•	LED	I
•	EMC	FCC, 15, IEC60825-1, EN55022 B
•		•
•		-20, +60°C, -4, 144
•		-30, +70°C, -22, 158
•		5 - 95
•		1.5, 5.0
•	IP	IP54
•		•
•		•
•		156 * 68 * 83
•		195
•		48 * 36 * 47CM, 20, 13.5
•		48 * 39 * 52CM, 30PCS, 15KG



