

USB 1d

M / N OCBS-C006



□□□

u 2500□□CCD□□□

□□|280□□□

□□□□□□□□□□□

□□□□3□□□□□□□

□□□□□□□□□□□

□□□□/□□/□□□□□□

□□□□□□□□□□□□□

!□□□□□□□□□□□□

□□□□	□□□	32□ARM□□□
□□□□	□□□□□	2500□□CCD□□□
	□□	LED□□□660nm±10nm□
	□□□□	□□280□□□
	□□□□	□□±55°□□±25°□□±75°
	□□□□	□60□□□□□□25mil□40cm□□15mil□32cm□□10mil□22cm□□5mil□11cm□□3mil□3cm
	□□□□	≤110□□
	□□□	≥0.1mm□400□□
	□□□□□	15□
	□□□□	□□39□□□ASCII□□39□□□32□□□128□□□93□□□11□Codabar / NW7□
		□□UPC / EAN / JAN□□□EAN-13□EAN-8□UPC-A□UPC-E□EAN-128□□5□□□2□5□STD 2□5□□□2□WPC□□
		□□2□5□□□Pos□□IATA□MSI / PLESSY□□□□□□□□□2□5□BC-412□ UPC-A□UPC- E□Code 128□Code 93□Coda bar□IATA□MSI / PLESSY□Code 32□STD

電圧	入力	4.5V~5.5V(V \pm 5%)	
	最大電流		100mA/110mA
	待機電流		30mA/40mA
寸法	本体サイズ	170mm×60mm×95mm	
	重量	185g	
	筐体材質	ABS	
	接続方式	USB	
動作環境	動作温度	-20°C~50°C	
	保存温度	-40°C~70°C	
	湿度	0%~98%	
	落下耐性	0~70,000回	
読取能力	5桁UPC	40mm-160mm	
	1000桁Code93	20mm-240mm	
	1500桁EAN13	40mm-250mm	
	2000桁128	40mm-380mm	
	4000桁128	80mm-520mm	





OCBS-C006





OCBS-C006



