

**USB**  
**OCBS-2008**

**□□□□**

□□□□□□;  
 □□□□□□□□;  
 □□□□□□□□□□□□□□;  
 □□□□□□□□□□□□;  
 4mil□□□□□□□□;  
 □□□□□□□□□□□□;  
 SDK / API□□;  
 □□□□□;  
 □□□□□□

**□□□□**

□ □ □ □	
□□□□	USB,USB COM(□□□□)
□ □ □	640*480,256 gray levels.
□□□□□□	300□/□
□□□□	Australian Post□Aztec□BPO□Canada Post□Codabar□Codablock□ Code 11□Code 39□Code 93□Code 128/EAN128□DataMatrix□ Dutch Post□EAN.UCC Composite□Interleaved 2 of 5□Japan Post Matrix 2 of 5□MaxiCode□MicroPDF417□MSI Code□PDF 417□ Planet□Plessey Code□Postnet□QR code□GS1 □□RSS□□ Standard 25 Telepen□TLC 39□UPC/EAN
□□□□	≥4mil
□ □	□□□□630nm±10nm
□□□□	Code 39 □5□□□□50□□~120□□ Code 39 □10□□□□25□□~250□□ UPC/EAN (13□□)□20□□~320□□ Data Matrix(7.5□□)□63□□~150□□ PDF417(6.6□□)□62□□~145□□
□□□□□□	□□ ±45° @0°Roll and 0°Skew □□ ±30° @0°Pitch and 0°Skew □□ ±45° @0°Roll and 0°Skew
□□□□	≥30% □□□□
□□ / □□□□	
□□□□	□□+5V+5%
□ □	□□□□ 300□□ □□□□ 40□□ □□□□ 60□□ □□□□ ±10%
□□□□	156*68*83 mm
□ □	195g □□□□□□
□□□□	48*36*47CM □20pcs □□□13.5KG□ 48*39*52CM □30pcs □□□□ 15KG □
□□□□	
□□□□	-20°C ~ +60°C(-4 °F to 144°F)
□□□□	-30°C ~ +70°C(-22°F to 158°F)
□□□□	5% ~ 95% □□□□□□
□□□□□□	□□□□□□□□□□□□

□□□□□□

✘

✘

✘

✘

✘

✘

✘

✘

✘