

USB QR OCBS-2103

功能

- /□□□□;
- ;
- LED / LCD□□□□□□□□

规格

| | | |
|--------|----|---|
| □□□□ | | |
| □□□□ | | IOTC 0370 CHIP |
| □□□□ | | 640×480□CMOS |
| □□ | | RS-232□9.6□115.2Kbps□□□□USB 1.1□HID-KBW□HID-POS□ |
| □□ | 2D | PDF417□Data Matrix□QR□ |
| | 1D | EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Coda bar, Code 128(Include FNC1 FNC2 FNC3 subset), Code 93, ITF-6, ITF-14□Interleaved 2 of 5,Industrial 2 of 5□Standard 2 of 5, Matrix 2 of 5□GS1 Data bar (RSS-Expand, RSS-Limited, RSS-14),Code 39(Include Code 39 FULL ASCII),Code 11,MSI-Plessey |
| □□□□ | | ≥10□ |
| □□ | | □□LED |
| □□□□ | | □□□□□□□□□□ |
| □□□□ | | 10□ |
| □□□□□□ | | ≥30□ |
| □□□□ | | □□□68°□□□□42°□□□□54° |
| □□ | | 0 - 100000 LUX |
| □□□□ | | 1 W |
| □□ | | DC 5V□0.5A□AC 100□240V□50□60HZ |
| □□□□ | | □□□□□□□□ |
| □□ | | 127.3□□□L□X111.5□□□W□X94□□□H□ |
| □□ | | 300□ |
| □□ | | |
| □□□□ | | -10°C□+ 50°C |
| □□□□ | | -20°C□+ 60°C |
| □□ | | 5□ - 95□□□□□□□□ |
| □□□□ | | □□□□□□□□□□uTools□□□□ |
| □□ | | FCC□15□B□□CE EMC B□ |