

OCBS-W230

OCBS-W230

OCBS-W230

OCBS-W230 distance 300M 1m

OCBS-W230 distance 300M 1m

OCBS-W230 distance 300M 1m

OCBS-W230 distance 300M 1m

OCBS-W230 distance 300M 1m

OCBS-W230 distance 300M 1m

OCBS-W230

0000	617mmLED		
0000	625mmLED		
0000	39°H×25°V		
0000	0 - 360°		
00	±65°		
00	±60°		
00000	25		
1D	UPC / EANUPC / EANBooklandEANISSNUCCCode128GS1-128ISBT 1283939ASCII Trioptic 393293Code112 52 52of 552GS1Barvariants3 5ISBT Concat		
2D	PDF417MicroPDF417TLC-39MAXICODEQRMicroQR		
00	USB		
0000	1300m		
0000	-10° - 45°		
0000	-20° - 65°		
0000	5-85		
0000	5-95		
000	1.8		
0000	DC 5V350mA		
Lumination	3.000 LUX;86000LUX		
EMC	EN50081PAR1		
FCC	EN50082PAR1		
IP00	IP42		
00000			
0000*	HD		
0000			
39	5.0	5	90
100UPCA	13.0	8	200
39	20.0	8	250
PDF 417	6.8	5	95
0000	10.0	5	110
QR	20.0	10	150
0001D39	2.80.071		
0000000	4.80.122		
00	ABS + PC		
00	95x65x155mm		
00	160		
00000	18.2X11.7X11.2cm		
00000	374		



