

1D / 2D

OCBS -2015

-

300 DPM OCR

-

-

40 100

-

1.8 IP42

-

-

USB

	CMOS	*	≥300

尺寸	1280 * 960	重量*	2 m / 箱
光源	LED / 白光LED	照度	40.5° 30.4°
波长	650nm	功率*	≥25W
功能	2D	PDF417 QR 条形码	
	功能	EAN-13 EAN-8 UPC-A UPC-E ISSN ISBN Codabar Code 128 Code93 ITF-6 ITF-14 5 2 5 2 5 2 5 Matrix2 GS1 MSI-Plessey Plessey	
规格*	尺寸	2015-1	2015-2
	EAN-13 1300	25 155	40 410
	39 500	50 100	110 250
	PDF 417 670	40 105	115 190
	1000	40 110	100 250
	1500	35 155	70 280
角度*	角度	±50°	
	角度	360°	
	角度	±50°	
接口			
接口	RS-232 USB PS / 2	接口	LED
尺寸	166 * 107 * 71 mm	电压	5 VDC ±5%
功率	208W	功耗	1251 mW
5 VDC	266 mA	功耗	109W
环境			
温度	-20°C ~ 50°C	湿度	±16 kV ±8 kV
温度	-40°C ~ + 70°C	防护	1.8m
防护	5 95	IP	IP42
认证	FCC Part15 B CE EMC B		
接口			
接口	USB	USB	
	RS-232	RS-232	
	PS / 2	PS / 2	
电源	5V RS232 DC 5V 1.5A AC100 240V 50 60Hz		
其他			
重量	重量		
重量	重量		



OCBS-2015





OCBS-2015





OCBS-2015





OCBS-2015





OCBS-2015

