

80mm

OCPP-M086



OCPP-M086



□□□

□□Windows□Java□Android□IOS□

□□□wifi□USB□RS232□□□□□□□□

□□□□□□□□pos ri□□□□□□□□

□□□□□□90mm /□□

TPH□□□□100□□□

□□□□□□□□□□

□□□□□

□□□□□×□×□□	98×103×45□□
□□	280□
□□	□
□□□□□□	72□□
□□□□	□□□□
□□□□	□□ESC / POS□□□□
□□□□	□□90mm /□
□□□	8□/□□□203 dpi□
□□□□	12x24 / 24x24
□□□	48□/ 24□
□□□□	1.5 x 3.0□□□□×□□/ 3.0x3.0□□□□×A□
□□□□	80.0±0.1□□x 40.0□□□□
□□□□	0.06□0.08□□
□□□	□□□□/□□□□
□□	USB□RS-232□□□□□wifi□□□□
□□□□	□□5 KB□□

電圧	9V DC / 2A
電流	7.4 V / 2000 mA; 4-5mm幅用 120-150mm巻
寸法	約100mm幅
動作温度	約-10°C ~ 50°C 約10mm幅
保管温度	約-20°C ~ 70°C 約5mm幅



# OCPP-M086





# OCPP-M086





OCPP-M086





□□□□□□



□□

## ▶ Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant

