

W600



CHARACTERISTICS	
Color	White VLD @ 650nm/670nm
Dimensions	164mm*67mm*95mm W * H * D
Dimensions	130mm*45mm*129mm W * H * D
Material	ABS + TPR / PC
Weight	235g
Power	0.5W
Light Source	LED
Beam Angle	60°

CHARACTERISTICS	
Beam Angle	60° @ 30cm, 98° @ 100cm
Beam Diameter	2.5-600mm @ 0.9mm/0.25mm
Beam Diameter	100mm
Beam Diameter	0.10mm/4MIL PCS0.9
Beam Diameter	1 / 500mm
Barcode	UPC / EAN, UPC / EAN, UCC / EAN, 128, 39, 39, ASCII, Trioptic 39, 128, 128, ASCII, 5, 2, 5, 93, 11, RSS, 2, 5
Battery	3.7V / 750mAh
Battery	3.0V
Battery	30min
Battery	0.5W; 4000mAh
Beam Angle	60°; 45°
Beam Diameter	30mm
Beam Diameter	2.4G
Beam Diameter	USB

CHARACTERISTICS	
Temperature	0 to 50°C, -40 to 70°C
Humidity	5-90%
Light Intensity	1.5 Lux
Light Intensity	0-10 LUX
Electrostatic Discharge	±12KV, ±6KV
Compliance	CE, FCC, RoHS



