

# Android Pos / Windows Pos

M / N POS -D11.6-W / A



□□□

I Windows / Android □□□□□□

I Windows □□□ Intel Apollo N3450 □□ 2.0GHz CPU

I □□□□□□□□ MT6797 Decuple 2.3GHz CPU

I 4GB RAM + 64GB SSD □ Windows □

I 3GB RAM + 64GB eMMC □ Android □

I 11.6 □□□□□□□□□□

I 58 □□□ 80 □□□□□□□□□□□□

□□□□□

I □□□□□□□□□□□□□□□□□□□□

I □□□□□□□□□□□□□□□□□□□□

I □□□□□□□□□□□□□□□□□□□□

I □□□□□□□□□□□□□□□□□□□□

□□□

□□	POS -D11.6-W / POS -D11.6-A
□□①	□□□Apollo N3450□□2.0GHz CPU□Windows□
□□②	CPU□MT6797 / GPU□T880 780MHz□□
OS①	Windows7□□□□□
OS②	Android 8.0
□□①	4GB RAM + 64GB SSD□Windows□
□□②	3GB RAM + 64GB eMMC□Android□□□□□□4GB RAM
□□□	□□□□□□
□□□□	11.6□□□16□9
□□□	1920 * 1080P□□□□□□
□□	7000□□
□□	□□
□□□	58mm□□□□□□□□□□□□□□80mm□□□□□□□□□□
□□□①Windows□	USB / HDMI / USB-A * 2
□□□②Android□	TYPE-C /HDMI/USB-A*2/3.5mm□□/ TF□□
□□□□	0°C□40°C
□□□□□□Android□	GSM□B2 / 3/5/8 CDMA1X□BC0 WCDMA□B1 / 2/5/8 CDMA2000□BC0 TD-SDMA□B34 / 39 FDD-LTE□B1 / 3/4/5/7 // 20 TDD-LTE□B38 39 40 41 □□4 .0 + EDR WIFI 802.11 a / b / g / n / ac
□□□□□□□□□□	□□□DC□□□USB2.0x3□RJ45X1□58 / 80□□□□□□□□≤60mm□ □□□MSR /□□/ RFID / RS232
□□□□	-20°C□60°C
□□□□□□	110-240V / 50-60HZ□□□□□□□□12 / 24V□□□□□□□□□□











□OEM / ODM□

□□□□□□□□



## ▶ Company



## ▶ Certificates



## ▶ Payment





