

□□□□12V / 24V□□□□

□□□□ECD410D □

□□□□

4□5□□□□□□□□8□□□□□□□□

□□□□□□□□□□□□□□□□□□

9V□24V□□□

□□□□□□□□□

□□3□□□

□□□

□□□	□0.8mm□ SPCC□□□□□□□□□□
□□□	□□□1.0□SECC □□□□
□□□	□□□□ □□85/84/84/85□□
□□□	□□□ □□68/67/67/67/68□□
□□□	□□193□□; □□□59□□
□□	8□□□ □□□□82;□□□57;□□□46
□□	3□
□□	12V 24V□□□
□□□	□□□□□ □□□□
□□	RJ11 / RJ12
□□	□□□□□
□□	6.5□□□□□□7.0□□ □□□
□□	410□W□×415□□□× 100□□□□□□□□10□□□□□

□□□



# ECD-410D



[www.ocominc.com](http://www.ocominc.com)





[www.ocominc.com](http://www.ocominc.com)





## Application Area

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

