

58

OCPP - M06

000

00000x0x00	105 * 75 * 45mm
00	134
00	00
0000	0000
0000	0000ESC / POS00
00000000	4800
0000	009000/0
000	8 / mm 203 dpi
0000	12x24 / 24x24
000	32 / 16
0000	1.5 x 3.0 mm 00x00/3.0 x 3.0 mm 00x00
0000	58.0±0.1mm x 40.0mm
0000	0.06 0.08
000	0000/0000
00	USB RS-232 0000 000000
00	256KB
000000	9 V CC / 2 A.
000	7.4 V DC / 1500 mA; 0000004-50000000000000000000120-15000000
0000	000000 000000
0000	000-10 50 0000 00010 90
0000	000-20 70 0000 0005 95
0000pos000dis	0030 ASCII 000000000000000000000000
00	00000000 "1234" 000000 000000000000 006000
00000000	3.5 * 1.1
0000	00CPP-M06-BB 00ndroid 00 üSB + COM + 00000000
	00CPP-M06-BB-AI 00ndroid + IOS 00 üSB + COM + 00000000
	00CPP-M06-B 00ndroid 00 üSB + COM + 00000000;
	00CPP-M06-U 00ini 0000 00ndroid 00 üSB + COM 00000000
	00CPP-M06-BB-AA 00ndroid + IOS 00 üSB + COM + 00lueetooth 00battery 007 dis pos itivi Android Android +1



www.ocominc.com







www.ocominc.com



Global Fortune 500 1 100

12 + 1 pos 24;

30 DOA DOA

pos

4.

T / T LC Western Union Escrow T / T Western Union Escrow Paypal pos Moneybookers Visa MasterCard Maestro Solo Carte Bleue Pos tePay CartaSi 4B Euro 6000

5.

6.

Eruopean ...

159 2200 500 O2 50

OCOM

- 500 POS Auto-ID
- 1 O2 Star
- 2200 159;
- 11 OEM / ODM
- POS
- pos ta res
- ISO FCC CE Soncap POA BIS
- 12 + 1
- “ ”
-