

**1**

- position;
- LY;
- ;
- ;
- BMP PCX BAC
- S.erial + USB + LAN**
- PDF417 QR DOTMATRIX;

**2.Specifications**

	OCBP - 005
	203 DPI 8 / mm
position	
	127 / ; 50.8 /
	16 76
	25 ; 80
	0 8 ;
	1 1 0 ; 0 90 180 270 360
	&
	2MB 2MB DRAM
	PCX BMP FLASH DRAM
	CODE128 EAN128 ITF Code39 Code93 EAN13 EAN13 + 2 EAN13 + 5 EAN8 EAN8 + 2 EAN8 + 5 CODABAR POS TNET UPC-A UPCA + 2 UPCA + 5 UPC-E UPCE + 2 UPCE + 5 C POS
	T MSI MSIC PLESSEY ITF14 EAN14 PDF417 QR DATMATRIX
	USB + RS232 + LAN USB
	24VDC 2.5A
	5 C 45 C
	-40°C C 55 C
	20 ~ 80
	< = 93 40 C
	D220mm * H148mm * W150



OCBP-005





OCBP-005





### 3. 安裝



### 4. 安裝



### 5. 包裝及規格

包裝

包裝規格

包裝規格 30X23X45mm

重量 2.67 KG

包裝規格 6個裝包裝規格 30 \* 23 \* 20mm 重量 2.67kg 包裝規格 70 \* 34 \* 45mm 重量 19.02kg

包裝

包裝規格 DHL 包裝規格 UPS 包裝規格 EMS 包裝規格 TNT

