High quality handheld mobile android POS terminal machine(POS-T8)

Features:

- 1. Android 4.4 operation system.
- 2.Adopts Qualcomm quad-core 1.2GHz processor.
- 3.4.0 inches IPS capacitive touch screen.
- 4. Safety and reliable design
- 5. Passed Unionpay Pboc L1 & amp; L2; passed PIN input safety certification.
- 6. Unionpay direct connect POS network access.
- 7. Support Pirnting Receipt and Barcode reading
- 8. Supports magnetic stripe card, IC card, contactless card.

Specifications:	
System Parameters	
CPU	Qualcomm quad-core 1.2GHz
OS	Android 4.4
RAM / ROM	ROM 4GB eMMC; RAM 512MB / 1GB DDR2;
	support external micro SD card, 32 GB at most
Display	4.0 inch capacitive, multi touch; 480 * 800, IPS display
Keypad	3 Touch System Keys, 15 physical keys (include Power key, Custom key, POS Cipher
	key and Command key)
Battery	Lithium polymer battery, 4000mAh
Functional Configuration	·
Camera	Rear Camera 5M AF (support flashlight), Front Camera 0.3M wide angle
Printer	Built-in 2 inches thermal printer
Navigation	Built-in GPS, support AGPS
Indicator Light	System indicator light, POS indicator light
Audios	Built-in speaker, buzzer, microphone, vibrator
Sensors	Gravity sensor
POS	·
Sound Wave Payment	Support
Magnetic Strip Card	Triple track MSR, bi-directional swiping ISO7811, 7812
IC Card	1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV
Contactless card	13.56MHz, ISO / IEC 14443 Type A / B, qPBOC
SAM Card	1 SAM Solt, ISO7816
Cipher Keyboard	Built-in keypad
Network Parameters	
Network Type	WCDMA / GSM
Network Spectrum	WCDMA 2100MHz
	GSM / GPRS / EDGE 850/900/1800 / 1900MHz
WLAN	802.11 a / b / g / n Built-in Antenna
Voice / Data Service	Support
WPAN	Bluetooth V4.0 + EDR
External Interface	
USB Interface	Micro USB2.0, support USB OTG
Charger Jack	DC JACK
Power Supply Jack	Pogo Pin, 5V - 500mA
Communication	USB, RS232

Physical Parameters		
Dimensions	205mm H * 82mm / 67mm W * 33mm D	
Weight	500g (battery included)	
Operating Temp	-20 ° C ~ 60 ° C	
Storage Temp	-40 ° C ~ 80 ° C	
Humidity	10% ~ 90% RH non-condensing	
Drop Test	1.0-meter drop protection	
Roller Drop Test	500 times	
ESD protection	± 8KV contact discharge; ± 15KV air discharge	
Development Environment		
System Environment	Android 4.4 / SP-UI	
Development Environment	SDK	
Management Software	PC management suite / MDM	

Power adaptor for option:

Europe, British, America, Australia, Asia etc.

Production capacity and lead time:

We have strong production capacity;. We can produce thousand of printers and barcode scanners per day Normally, our lead time between 1-5 days.

Shipping method:

Air, Sea, Express (DHL, FedEx, UPS, EMS, TNT and so on)

Warranty:

12 + 1 months of shipment normally. Some designated models can have as long as 24 months warranty. Spare parts can be provided for mass order.

Payment term:

T / T in advance, Western Union, PayPal, Escrow, L / C, Cash, etc