

1D / 2D

M / NOCBS -W233

	CMOS. 5600KLED
	32
	1MP1280 * 800
	2.4g + USB2.4G + + USB
	2DPDF417Micro PDF 417QRQR1 / 2MicroAZTEC
	1DUPC-AUPC-EEAN-8EAN-13CODE128CODE39CODE 93 CODE32CODE11CODABARPLESSEEMSI25IATA 2 ON 5 225PharmacodeRSS-14RSS-14RSS-14 LimitedCOM pos ITE Code-A COM pos ITE Code-B COM pos ITE Code-C
	1D≥40.10
	2D.≥70.10
	39-5MIL60mm-120mm
	UPCA-13MIL10035310
	1/8
	≥ 30.
	5555°
B.at	2000 MAH30000
	5 VDC±10
	250mA±5
	0.°C+ 50°C
	- 40°C+ 70°C
	5 - 95
	CEIP.54rohsfccCEMREDLVD
	275G.
	190 mm * 115 mm * 85 mm;
	50/ CTN; 16 kg / ctn;
	600 mm×450 mm×420 mm



OCBS-W233





OCBS-W233





OCBS-W233



OCBS-W233



OCBS-W233



OCBS-W233





OCBS-W233





OCOM POS ID 500

2007 6 OCOM ISO9001 2015 159 2600 50 02

OCOM “ ” OEM / ODM

There is a Trust called OCOM

