

OCBS-LA06

OCBS-LA06

OCBS-LA06	
OCBS-LA06	650-670nm
OCBS-LA06	100
OCBS-LA06	2.5 600 100 UPC / EAN
OCBS-LA06	
OCBS-LA06	0.10 4MIL PCS 0.9
OCBS-LA06	20%, @ 650nm
OCBS-LA06	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
OCBS-LA06	
OCBS-LA06	PS2 RS232 USB
OCBS-LA06	DC + 5V +/- 5
OCBS-LA06	100
OCBS-LA06	<40
OCBS-LA06	RS232
OCBS-LA06	45° 60°
OCBS-LA06	L165.42mm xW69.72mm xH89.67mm
OCBS-LA06	140
OCBS-LA06	
OCBS-LA06	
OCBS-LA06	
OCBS-LA06	0 ~50 degree eC
OCBS-LA06	-40~70degreeç
OCBS-LA06	5~95
OCBS-LA06	±15kV +8KV
OCBS-LA06	1.5
OCBS-LA06	
EMI / RFI	FCC A CE
OCBS-LA06	CDRH 2

OCBS-LA06

