□□□2015□□□□□□□□□□□□

□□□□□

□□□2015□□□□□□□□□□□□
□□□□□□□□□□□
CPU□16□
□□□□□100□/□
□□□□□□□□
□□□□□□□LED□
□□□PS2 / RS232 / USB□□□
□□□□□/□□□□□

□□□□□

□ □□	
□ □□□□□	□□ □□□650□□□
□□ □□□	100 □□□□
□□ □□	10 □520□□□100□UPC / EAN□
□□□□□□	□□
□□□□	0.10□□□4MIL□
□□□□□□□□	30□□□□□□□□@□650nm□
□□□□	3000000□□1
□□□□□	UPC-A□UPC-E□□□2 5□□□2 5□EAN8□EAN 13□□128□□EAN 128□39□□93□□□□□125□ MSI / Plessey□□□
□□□□	
□□□□□□	PS2□RS232□USB
□□□	5V
□□□□□	120□□
□□□□□	<30□□
□□□	□□□□□□□□RS232□□□
□□□	□□45°□□60°
□□□	L175mm X W70mm X H100mm
□□□	150□□□□□□□
□	□□
□□□	□□□□□□□□
□□□□	
□□□□□	-20 - 45□□□
□□□□□	-20 - 45□□□
□□□	5□85□□□□□□□□
□□□□□	□□□+/- 15kV□□□□□+/-□□□□8KV□
□□□□□	□□□□□1.5□ □□□□□□□
□□□	
EMI / RFI□	□□EN50081.parl□□
□□□□□	□□□□IEC 60825-1□□□2□

□□□□□

1.□□□□□□□□□DHL□□□□□□UPS□EMS□TNT□□

2.[illegible]3-7[illegible]

3.[illegible]2-4[illegible]

4.[illegible]

[illegible]

1. T / T[illegible]

2.[illegible]

3.[illegible]

4.[illegible]

5.[illegible]L / C

[illegible]

[illegible]

[illegible]

12[illegible]24[illegible]

RMA[illegible]

[illegible] [illegible]RMA[illegible]OCOM[illegible]30[illegible]/[illegible]

[illegible] [illegible]DOA[illegible]

[illegible]30[illegible]DOA[illegible] DOA[illegible]

[illegible]

OCOM[illegible] [illegible]POS[illegible] OCOM[illegible]R&[illegible]; D[illegible]