

USB VFD VFD220A

Spec

|                       |                                         |
|-----------------------|-----------------------------------------|
| Interface             | RS-232C                                 |
| Baud Rate             | 9600                                    |
| Parity                | 2000CD                                  |
| Stop Bit              | 8                                       |
| Flow Control          | 1                                       |
| Power Supply          | DC12V 4PS                               |
| Display Type          | VFD                                     |
| Display Size          | 2" x 20" / 40" x 5" x 7"                |
| Resolution            | 160 x 23.8 mm H                         |
| Character Size        | 11 x 7 mm                               |
| MTBF                  | 25000                                   |
| Dimensions            | 80 mm H x 225 mm W x 37 mm D            |
| Weight                | 480 g                                   |
| Viewing Angle         | 225 mm H x 185 mm L x 95 mm W x 25 mm H |
| Viewing Distance      | 45°                                     |
| Response Time         | 1.2 ms                                  |
| Operating Temperature | -20 ~ 70 A18                            |
| Storage Temperature   | -40 ~ 80 A19                            |
| Humidity              | 10 ~ 85%                                |
| Shock                 | 10 ~ 90 g                               |
| Compatibility         | ESC / POS, DOS, Windows                 |
| Notes                 |                                         |

Warning

XXXXXXXXXXXXXXXXXXXX