

OCPP-585

OCPP-585

OCPP-585

| | |
|----------|---|
| OCPP-585 | OCPP-585 |
| OCPP-585 | 384/203DPI |
| OCPP-585 | 384/ANKA12 * 241.5W* 3.0Hmm /24 * 243.0W* 3.0Hmm |
| OCPP-585 | JAN13EAN13JAN8EAN8CODE39 QR CODE |
| OCPP-585 | PERSON ESC / POS |
| OCPP-585 | OCPP-585 |
| OCPP-585 | 90mm / sec |
| OCPP-585 | 57.5±0.5mm |
| OCPP-585 | 0.06-0.08mm |
| OCPP-585 | 50 |
| OCPP-585 | 190 * 132 * 119mm |
| OCPP-585 | 1.2KG |
| OCPP-585 | OCPP-585 |
| OCPP-585 | OCPP-585 |
| OCPP-585 | Φ50mm |
| OCPP-585 | USB + |
| OCPP-585 | Win 9X Win 2000 Win 2003 Win XP Win Vista Win 7 Win 8 Win8.1 win10 ESPON |
| OCPP-585 | AC 110V / 220V 50-60Hz |
| OCPP-585 | DC12V / 3A |
| OCPP-585 | DC12V / 3A |
| OCPP-585 | DC12V / 1A |
| OCPP-585 | 0-45°C 10-80 |
| OCPP-585 | -10-60°C 10-90 |
| OCPP-585 | CE / FCC / CCC / RoHS |

OCPP-585

OCPP-585



OCPP-585

*OCPP-585

*OCPP-585

*OCPP-585

*OCPP-585 WinXP Win2000 WinVista Win7 Win8-32bit

*OCPP-585 Win7and Win8-64bit

*Linux

*

*USB Printdemo

*Android SDK

*