

!!! pos 80 usb OCPP 88A

OCPP-88A

Resolution	576dots / (dots) 512dots / ; 24 x 24 dots 18030 dots Hong (dots)	
Dimensions	W: 12 * 24dots 1.5 (W) * 3.0 (H) ; H: 9 * 17dots 1.1 (H) * 2.1 (H) ; W / H: 24 * 24dots 3.0 (W) * 3.0 (H) ;	
Barcode	JUPC A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / ITF / CODE39 / CODE93 / CODE128 QR	
Capacity	250 / 300	
Interface	USB + USB LAN + USB + USB +	
OS	ESC / POS	
Software	Win9X / XP / VISTA / WIN2000 / Win2003 / 7 / 8 / win8.1 / Linux ESPON SDK	
Weight	79.5 ± 0.5 (72)	
Temperature	83	
Humidity	0.06-0.08	
Power	(W)	
Current		
Voltage	24V / 2.5 A	
Power	0-45	
Humidity	10-80%	
Dimensions	190 * 145 * 145 (MM)	
Weight	1.60	
Model	P / N	
	OCPP-88A-U	USB
	OCPP-88A-UR	USB +
	OCPP-88A-UL	USB + LAN
	OCPP-88A-URL	USB + LAN
	OCPP-88A-W	+ USB
	OCPP-88A-UR	+ USB +
	OCPP-88A-U0	USB
	OCPP-88A-UR0	USB +
	OCPP-88A-ULO	USB + LAN
	OCPP-88A-URL0	USB + Lan
	OCPP-88A-W0	+ USB
	OCPP-88A-BUL0	+ USB + LAN

- ✘
- ✘
- ✘
- ✘
- ✘
- ✘
- ✘
- ✘
- ✘



□□□□:

\*□□

\*□□□□

\*□□

\*□ WinXP Win2000 □□ Win8 32 □□□□□

\*□□□□ Win7 □ Win8-64 □

\*Linux □□□□

\*□□□□□□□□

\*USB Printdemo(□□□□□□□□)

\*SDK □□□□

\*□□□-□□