

LED POS

□□□□

LED POS

8 LED

□□□□

360

“ESC / POS”

□□□□

| | |
|----------|--|
| □□ | |
| □□□ | RS232 □□□ USB □□□ DC □□□ |
| □□□□ | 2400 / 9600BPS |
| □□□ | 1500cd |
| □□□□ | □□ |
| □□ | DC5V □□□□ USB □□□ |
| □□□ | LED □□□□□□□□□□ |
| □□□□□ | 8 □□□□ 0 □ 9 □ |
| □□□□□ | 160 □□ × 30.8 □□ |
| □□□□□ | 13MM * 7.6 □□ |
| MTBF □ | 25000 □□ |
| □□ | |
| □□□□□ | 224 □ L □□ × 88 □□□ mm |
| □□□□□ | □□□ 400 --- 442 □□ □□ 185 □ L □□ × 95 □ W □ X 25 □□□ mm |
| □□□□□□□□ | 8° □ 120° |
| □□ | □□□□□ |
| □□□ | 520 □□□□□□□□; 850 □□□□□□□□; 1100 □□□□□□□□ |
| □□□□ | 255 □□□ × 210 □□□ × 96 □□□ mm |
| □□ | |
| □□□□□ | -40°C -- 50°C |
| □□□□□; | -60°C -- 80°C |
| □□□ | 30 □ - 85 □ |

□□□□□□□



□□□□

□□□□□□□□□□ □□□□ □

□□

□□□□

□□

