

2D

OCBS -2017



-
-
- 4mil
-
- 1D 2D
-

	USB; USB COM; RS232
	Linux Android Windows XP 7,8,10 Mac
	CMOS
	LED + LED
	32 ARM MCU + DSP
	≥4mil PCS90 39
	1/5
	25cm / s.
	LED
	≥25
	ABS + PC.
	DC 5V±5
	375MW; 226MW; 750MW
	289g±5g
	L * W * H 180 * 115 * 85 mm
	60 * 45 * 38.5 cm 50 pcs / carton nw= 14.45kg gw= 16.15kg

□□□□	1D	●Code25□□●Code25□□●Code25-Matri ●Code39-Regular●Code39-Fullascii●Code32 ●Code93-Regular●Code93-Fullascii●Code128 ●EAN / GSL / UCC-128AUTO●CODABAR●MSI ●EAN / JAN-13●UPC-A●JAN-8●UPCE
	2D.	●QR●□□□□●PDF417
□□□□		ROLL360°□□□30°□YAW45°
□□□□		Code39 4.17MIL□15□□□□4cm - 8cm
		Code128 4.17MIL□16□□□□7cm - 15cm
		□□□□10.83mil□8□□□□3cm - 9cm
		□□QR 20mil□8□□□□1cm - 19cm
□□□□		
IP□□		IP42.
□□□□		0□50°C/ 32□122‰
□□□□		0□50°C/ 32□122‰
□□□□		20□□85□□□□□□
□□□□		20□□85□□□□□□
ESD□□		15kV□□□□
□□□		1.5M□□□□□□□□□□



OCBS-2017





OCBS-2017





OCBS-2017





OCBS-2017

