

2D

OCBS-2008

Features

-
-
-
- 4mil
-
- SDK / API
-
-

Specifications

| | | |
|---|-----|---|
| • | | • LED |
| • | | • |
| • | | • |
| • | | • LED |
| • | | • |
| • | | CMOS |
| • | | 640 * 480 256 |
| • | | 13mil UPC40 |
| • | | 50; 20 |
| • | | ≥4mil |
| • | 1D | UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN, EAN, Bookland, ISSN, 39, 39, ASCII, 32, Trioptic, 39, 5, 2, 5, 5, NW7, 128, UCC / EAN 128, GS1-128, ISBT 128, CODE93, 11, USD-8, MSI / Plessey |
| • | 2D | PDF417, MicroPDF417, QR, DataMatrix, Aztec, GS1 |
| • | | 39, 5mil, 50, 120 39, 10MIL, 25, 250 UPC / EAN, 13mil, 20, 320 7.5mil, 63, 150 PDF417, 6.6mil, 62, 145 |
| • | | ±45° @ 0° ±30° @ 0° ±45° @ 0° |
| • | | • |
| • | | USB, USB COM |
| • | | 3.3V, 5V DC |
| • | | 2.0, 400 |
| • | | 2.5, 450 |
| • | DC | 5.5V 1A |
| • | LED | I |
| • | EMC | FCC, 15, IEC60825-1, EN55022 B |
| • | | • |
| • | | -20, +60°C, -4, 144 |
| • | | -30, +70°C, -22, 158 |
| • | | 5 - 95 |
| • | | 1.5, 5.0 |
| • | IP | IP54 |
| • | | • |
| • | | • |
| • | | 156 * 68 * 83 |
| • | | 195 |
| • | | 48 * 36 * 47CM, 20, 13.5 |
| • | | 48 * 39 * 52CM, 30PCS, 15KG |



