

□□□□□□□□□□□□□□□□
 □M / N□OCBS-2010□

□□□
 □□□□□□□□;
 □□□□□□□□□□;
 □□□□□□□□□□□□□□□□;
 □□□□□□□□□□□□□□;
 □5mil□□□□□□□□□□□□□□□□;
 □□□□□□□□□□□□□□;
 □□□□□□;

□□□

□□□□	
□□□	640 * 480□ 256□□□
□□	LED□630□□±10□□□
□□	0□10□LUX
□□□□	□□□□SR□□□□4□ °;□□□□30 °
□□□□	25□□/□
□□	2D DataMatrix□□□5□MAXICODE□MicroPDF417□MSI□□PDF417□QR□□□□2 5□Telepen□TLC 39□□□□□2
	1D □□□□□□□□□□□□□□□□BPO□□□□□□□□□□□□Codablock□11□□39□□93□□128□/ EAN128□ □□□□□□EAN.UCC□□□5□□2□□□□□□□□□□□□Plessey□□□□Postnet□□□RSS□UPC / EAN□□ □□
□□	≥5mil□ □□□□□□□□□□
□□	360°
□□	65°
□□	75°
□□□□	
□□	RS232 / USB □□□□□□□□□□MS□Mac□□□□□□
□□	DC 5 V ± 5□
□□	300□□ □□□□ 40MA□□□□□
□□	1.5□
□□	150 G
□□□□	170□□□~x 100□□□~x 75□□
□□□□	
□□□□	-20°C□60°C□-4°F□144°F□

□□□□	-30°C□70°C□-22°F□158°F□
□□	5□ - 95□□□□□□
□□	□□ □120□□□□□□□ Floor

□□

✗

✗

✗

□□□□



