

1d 2d

OCBS -2017

4

1D 2D

	USB; USB COM; RS232
	Linux Android Windows XP 7,8,10 Mac
	CMOS
	LED + LED
	32 ARM MCU + DSP
	≥4mil PCS90 39
	1/5
	25cm / s.
	LED
	≥25
	ABS + PC.
	DC 5V±5
	375MW; 226MW; 750MW
	289g±5g.
	L * W * H 180 * 115 * 85 mm
	60 * 45 * 38.5 cm 50 pcs / carton nw = 14.45kg gw = 16.15kg
	1D. Code25 Code25 - Code25-Matri code39-rougher code39-fullascii code32 code93-rougher code93-fullascii code128 EAN / GSL / UCC-128AUTO CODABAR MSI EAN / JAN-13 UPC-A JAN-8 UPCE
	2D. QR PDF417
	ROLL360° 30° YAW45°
	Code39 4.17MIL 15 4cm - 8cm Code128 4.17MIL 16 7cm - 15cm 10.83mil 8 3cm - 9cm QR 20mil 8 1cm - 19cm

IP	IP42.
Temp	0~50°C/ 32~122%
Humidity	0~50°C/ 32~122%
Temp	20~85
Temp	20~85
ESD	15kV
Weight	1.5M





OCBS-2017





OCBS-2017





OCBS-2017



## ▶ Company



## ▶ Certificates



## ▶ Payment



