

XXXXXXXXXX

XXXX KB887

XXX

XX	XXXX X XXCARD XXXXXXXXX
XX	400
XX	150mm*110mm*62mm
XXXX	-20+60°C
XXXXX	200,000
XXXX	XXISO7816XXXXXXXXXXXXGSM 11.11SIMXXSAMXX
XXXX	70
XX XX	USBHIDXXXXXXXXRS232 XXT = 0XT = 1CPUXXXXXXXXXXXXXXXXXXXX115.200 bps XXXXISO14443 Type AType BXXXXXXXXXXXXMifare S50Mifare S70MF1ICL10 Mifare ProMifare desfireMifareXXAT88RF020XX1102
XXXX XX XXXX XX XX XX XX XX XX XXXX XXXX	T = 09600-38400bps T = 19600-115200bps XXXXXXXXXXXX 2M XXLEDXXXXXXXXXXXX LCD122 * 32,28XXXXXXXXXXXX XXXXXXXXXXXX15XXXXXXXXXXXX09XXXXXXXXXXXX3DESXXXXXXXXXXXX XX4KXXXXXXXXXXXXIDXXXXXXXXXXXX XX1 \ 2 \ 3XXXXXXXXXXXX Windows XP2003XX7XX8XX10 UnixLinux XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX