

# 58mm

(OCPP- m10)

:

- n
- n windows, Java, Linux, android , IOS
- n Android SDK, IOS CE
- n 57 \* 40
- n 8
- (7 , )
- n 2200mAh18650
- n 90/
- n 100km life;
- n
- n ESC/POS

:



# OCPP-M10



[www.ocominc.com](http://www.ocominc.com)





# OCPP-M10



[www.ocominc.com](http://www.ocominc.com)





□□:

□□□□	□□□□□□
□□□□	ESC/POS □□□□□□
□□□□□□□□	48mm
□□□□	□□90□□/□
□□	8□/□□ (203 dpi)
□□□□	12x24/24x24
□□□	32□/16columns
□□□□	1.5 x 3.0 □□ (W x H)/3.0x3.0mm (WxH)
□□□□	58.0±0.1mm x □□40.0mm
□□□□	0.06 □0.08mm
□□□	□□□□□/□□□□
□□	USB, rs-232,bluetooth □)
□□	256KB
□□□□□□	9V DC/2A
□□□□	2□3.8V 2200mAh18650 □□□□□□ to7.4V

| 0000  
0000  
0000  
0000  
00  
|

| 00000 m00000  
Temperature:-10~50 000, humidity:10%~90%  
Temperature:-20~70 000, humidity:5%~95%  
0000, 000000000, 000 30 ASCII 000  
00000000 "1234", 00000 000000000. 00006000  
|

00000000:



0000:

00000000000000, mini 000000000, 0000000, 000000000000000000000000000000, 000000000, 000000000, 0000, 000  
00000, 000000000000000000000000000000, 00000000000000000000



000:

000000 00000, 00000, 000000, pos 000, 00000, 00000, 00000, 00000, 00000, qr 0000, 00000, 00000, 00000,  
58mm 00000, 2inch 00000.