

## Bluetooth Thermal Receipt Printer

|                           |   |
|---------------------------|---|
| Overall Dimension (W×D×H) | 105×75×45mm   |
| Weight                    | 134g  |
| Color                     | Black   |
| Effective print width     | 48mm  |
| Print method              | Thermal line printing   |
| Print commands            | ESC/POS compatible command set  |
| Print speed               | Up to 90mm/sec  |
| Resolution                | 8 dots/mm(203dpi)   |
| Print font                | 12x24/ 24x24  |
| Column capacity           | 32 columns/ 16columns   |
| Character size            | 1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)   |
| Paper dimensions          | 58.0±0.1mm x diameter 40.0mm  |
| Paper thickness           | 0.06 to 0.08mm  |
| Character set             | Alphanumeric/ Chinese Kanji   |
| Interface                 | USB, RS-232, Bluetooth (optional)   |
| Flash                     | 256KB   |
| Power Adapter             | 9V DC/2A  |
| Battery Power             | 7.4V DC/ 1500mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper |
| Other features            | Paper detection, power detection, Manual shut down  |
| Working conditions        | Temperature:-10degree C~50degree C, Humidity:10%~90%  |
| Storage conditions        | Temperature:-20degree C~70degree C, Humidity:5%~95%   |
| Device name               | Can be customized, letter and digital for option, at max 30 ASCII characters.                         |
| Password                  | Enter default pairing code "1234", it can be customized. At max 6 digitals.                           |
| Power plug dimension      | 3.5*1.1mm   |

