

□OCBS-LA11□

×1.000000000000;;

2.000360000000;

30000001000/00000000;

4.000000;

 $5.KBW \square RS232 \square USB \square \square \square \square \square;$

6.

	650-670nm
	100 000
	2.5 []600[][]100[]UPC / EAN[]
	0.10\ \pi\delta\text{IL}\ \pi\delta\text{PCS 0.9}
	3000000 00@ 650000
	UPC / EAN UPC / EAN UPC / EAN
	□11□ATA□RSS□□□5□□□□2
	PS2[RS232[USB
	DC + 5V±5[]
	<4000
	□□ 45°□□60°
	L165mm X W63mm X H87mm
	1290 00000
	0°C∏40°C
	-40°C□60°C
	509500000 000
	000 +/- 15kV0000+/-0008KV
EMI / RFI□	FCC A CCE
	CDRH 20 000



Product Picture











All-round show





Parameter

Performance Charact	eristics	
Light Source:	Visible laser (650-670nm)	
Scan Rate:	100 scans per second	
Reading Distance	2.5 ~600mm (100% UPC/EAN)	
Scanner Type:	Bi-directional Bi-directional	of
Resolution:	0.10mm (4mil) at PCS 0.9	Ĭ
Print Contrast	30%, minimum reflective difference (@650nm)	
Minimum:		
Error Rate:	1/3000000	
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code	
	39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full	
	ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI,	
	code 11, ATA, RSS variants, Chinese 2 of 5	

Physical Characterist	cs
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current; COTTO	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165mm X W63mm X H87mm
Weight:	129g (without stand)
Stand	Optional
Color:	Grey and black
User Environment	
Operating	\0°C~40°C
Temperature:	inc.co
Storage Temperature:	-40℃~60℃
Humidity:	5~95% relative humidity, non-condensing
Electrostatic	Confirm to +/-15KV air discharge and +/-8KV of contact
Discharge:	discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

- 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on) 1.
- EXPRESS: around 3-7 working days to arrive 2.
- ocomin INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
- By sea: depend on which destination port

- 5. T/T
- 6. Western Union
- 7. Escrow
- 8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.











