

Android PDA

M / N OCBS -D7000



□□

Android 7.0

2 GB RAM 16 GB ROM

480 * 800 4.0 IPS WVGA

□□□□/□□□□□□□□

RFID LF / HF / UHF /□□

□□□□□□

□□4G / Wifi / GPS /□□

pos□□□□5 MP□□LED□□□□□□□□

3.7 V 5100 mAh□□□□□□□□

□□□□□□□□IP65 / 1.5 m

□□□	
□□□□	
□□	158mm□□x75mm□W□x28mm□D□±2□□
□□	□□□300□□□□□□□□□□
□□	□□□□4.0□□TFT-LCD□WVGA 480x800□□□□
□□□	LED□□
□□	3□TP□□17□□□□□□4□□□□□□
□□	2□PSAM□1□SIM□1□TF
□□	□□□□□□□□□□3.7 V□5100 mAh
□□□□	
□□□	□□1.3 GHz Cortex A53□□□□

OS	Android 7.0	
RAM	2 GB RAM 16 GB ROM MicroSD 32 GB	
OS		
Operating Temperature	-20°C 50°C	
Storage Temperature	-20°C 70°C	
Weight	95g	
Dimensions	5ft./1.5 m	
Protection	IP65 IEC	
Shock Resistance	±15kv ±8kv ±8kv	
OS		
Development Tools	HHW	
OS		
Development Tools	Android Studio Eclipse	
OS		
Network	WCDMA 850/1900/2100 TDD-LTE 38.39,40 FDD-LTE B1.2.3.4.7.20	
Network	IEEE 802.11 b / g / n	
Network	v2.1 + EDR v3.0 + HS v4.0	
Network	GPS A-GPS 5 m	
OS		
OS		
OS	Processor	N431x
OS	OS	
OS	CMOS 2D	N6603
OS	OS	PDF417 MicroPDF417 Com pos ite RSS TLC-39 Datamatrix QR Micro QR Aztec MaxiCode Pos Pos Pos ta Pos ta Pos ta Pos
OS		
OS	5.0	
OS	LED	
RFID		
RFID	Frequency	125KHz / 134.2kHz FDX-B / HDX
RFID	Standard	ISO 11784 11785
RFID	Speed	2000 10
RFID	Frequency	13.56
RFID	Standard	ISO 14443A 15693
RFID	Speed	2000 8
PSAM		
PSAM	ISO 7816	
PSAM	9600 19200 38400.43000 56000 57600 115200	
PSAM	2	
OS		
OS	OS	1 1xDC 1xUSB
OS		



OCBS-D7000





OCBS-D7000





OCBS-D7000



