

# RS232 / USB

## OCBS -T2001

### Product Description

1. 1D / 2D

1. 1D / 2D
2. 1D / 2D
3. 1D / 2D
4. Windows / Android / Linux

2. 1D / 2D

Resolution		640x480 CMOS
Barcode	1D	Code 128, UCC/EAN-128, AIM 128, EAN-8, EAN-13, ISSN, ISBN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2 of 5 (European Matrix 2 of 5), Industrial 25, Standard 25, Code 39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand
	2D	PDF417, QR, DATAMATRIX
Label Thickness		≥5mil
Label Size		QR: 30MIL (0-15CM) 128: 10MIL (0-12CM)
Label Angle		±60° @ 0° Roll / 0° Skew 360° @ 0° / 0° ±55° @ 0° / 0°
Label Length		≥30
Interface		RS-232 / USB
LED		
Environmental		
Protection		IP5X
Operating Temp		-20°C ~ 50°C
Storage Temp		-40°C ~ 70°C
Humidity		5 ~ 95%
Dimensions		
Weight		USB: 228g, RS232: 261g
Size		102 * 82 * 73 (L * W * H)
Power		
Voltage		5V ± 0.25V
Current		430mA
Power Consumption		Idle: <200mA; Active: 150mA ± 15mA; Sleep: 80mA ± 2mA

### Picture Show



OCBS-T2001





# OCBS-T2001





# OCBS-T2001





# OCBS-T2001





OCBS-T2001



## ▶ Company



## ▶ Certificates



## ▶ Payment



## ▶ Contact us



Moneybookers Visa MasterCard Maestro Solo Carte  
Bleue Pos tePay CartaSi 4B Euro6000

5.

6.

Eruopean

159 2300 02 500 ..... 50

OCOM

- 500 POS
- 02 Star .....
- 2300 159;
- 11 OEM / ODM
- POS
- 
- ISO FCC CE Soncap POA BIS
- 12 + 1
- “”
- 

OCOM Technologies Ltd. TUV POS Auto-ID

OCOM POS POS POS POS  
ISO CE FCC

OCOM “”