

RS232 / USB

OCBS -T2001

Product Description

1. 1D / 2D

1. 1D / 2D
2. 1D / 2D
3. 1D / 2D
4. Windows / Android / Linux

2. 1D / 2D

Resolution		640x480 CMOS
Barcode	1D	Code 128, UCC/EAN-128, AIM 128, EAN-8, EAN-13, ISSN, ISBN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2 of 5 (European Matrix 2 of 5), Industrial 25, Standard 25, Code 39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand
	2D	PDF417, QR, DATAMATRIX
Label		≥5mil
Label Size		QR: 30MIL (0-15CM) 128: 10MIL (0-12CM)
Label Angle		±60° @ 0° Roll / 0° Skew 360° @ 0° Roll / 0° Skew ±55° @ 0° Roll / 0° Skew
Label Thickness		≥30mil
Interface		RS-232 / USB
LED		
Protection		
IP Rating		IP5X
Operating Temp		-20°C ~ 50°C
Storage Temp		-40°C ~ 70°C
Weight		5g ± 95%
Dimensions		
Weight		USB: 228g, RS232: 261g
Dimensions		102 * 82 * 73 (L * W * H)
Power		
Voltage		5V ± 0.25V
Current		430mA
Power Consumption		Idle: <200mA; Active: 150mA ± 15mA; Sleep: 80mA ± 2mA

Picture Show



OCBS-T2001





OCBS-T2001





OCBS-T2001





OCBS-T2001





OCBS-T2001



▶ Company



▶ Certificates



▶ Payment



▶ Contact us

Moneybookers, Visa, MasterCard, Maestro, Solo, Carte Bleue, tePay, CartaSi, 4B, Euro6000

5.

6.

Eruopean

159, 2300, O2, 500, 50

OCOM

- 500 POS
- O2 Star
- 2300, 159;
- 11 OEM / ODM
- POS
-
- ISO, FCC, CE, Soncap, POA, BIS
- 12 + 1
- “”
-

OCOM Technologies Ltd. TUV POS, Auto-ID

OCOM POS POS POS POS ISO, CE, FCC

OCOM “”