

11

|           |                                                                                      |
|-----------|--------------------------------------------------------------------------------------|
|           |                                                                                      |
| OCBS-2088 |                                                                                      |
|           |                                                                                      |
| BSPC      |                                                                                      |
|           | <195<br>< 130 mA                                                                     |
|           | 3.3 VDC/- 10/500mA                                                                   |
|           | USB -COM RS232                                                                       |
| IED       |                                                                                      |
|           |                                                                                      |
| CMOS      | 640*480pixels0.3MP                                                                   |
|           | LED                                                                                  |
| A Light   |                                                                                      |
|           | 4                                                                                    |
|           |                                                                                      |
|           | 1 2 m                                                                                |
|           | ≥15                                                                                  |
|           | 1D1DGS1 Databar™<br>2dmaxi;hanxin; MICROQR<br>GS1GS1GS1GS1<br>MicroPDF417; PDF417    |
|           | 13 EAN-13 55- 380m m<br>15 CODE 128 45- 480<br>500 39 35- 170<br>15 2 5- 340<br><br> |
|           | 0-360°;±60°;YAW±60°                                                                  |
|           |                                                                                      |
|           | 126 g                                                                                |
|           | 160* 64* 86                                                                          |
|           | 1 95 *1 05 *8 0 /0.256kg                                                             |
| 5 01      | 56 0* 41 0* 43 0m /14.1kg                                                            |
|           |                                                                                      |
|           | 0451080                                                                              |
|           | -20601090                                                                            |















**18+ YEARS**

OEM/ODM EXPERIENCES

**4000+**

CUSTOMERS OVER 165 COUNTRIES

**15,000,000+**

UNITS OF ACCUMULATED SALES

**CERTIFICATES**

BY ISO/CE/FCC/ROHS/BIS...



**CERTIFICATE**

