

□□□□□□□□□□

□□□

□□□□□□□□;

□□□□□□□□□□;

□□□□□□1D□2D□□□□□□□□□□;

□□□□□□□□□□□□□□□□;

5mil□□□□□□□□□□□□□□□□□□;

□□□□□□□;

□□□□□;

□□ □□		
□□□		640 * 480, 256 □□
□□		LED□630 nm±10 nm□
□□		0□100,000 LUX
□□□□		□□□□SR□□□□45°;□□□□30°
□□□□		25□□/□
□□	2D	DataMatrix□Matrix 2 of 5□MaxiCode□MicroPDF417□MSI Code□PDF417□QR □□Standard 2 of 5□Telepen□TLC 39□
	1D	□□□□□□□□□□□□□□□□BPO□□□□□□□□□□Codabar□ Codablock□Code 11□Code 39□Code 93□ Code 128 / EAN128□□□□□□□□□□EAN.UCC □□□□□□□□□□Interleaved 2 of 5□□□□□□ □□Planet□Plessey Code□Postnet□ RSS□UPC / EAN□□
□□		≥5mil□□□□□□□□
roll		360°
Pitch		65°
□□□		75°
□□□□		
□□		RS232 / USB□□□□□□□□□□□□MS□Mac □□□□□□
□□		DC 5 V±5□
□□		300□□□□□□□□40□□□□□□□□
□□		1.5□
□□		150□
□□□□		170□□×100□□×75□□
□□□□		
□□□□		-20°C□60°C□-4°F□144°F□
□□□□		-30°C□70°C□-22°F□158°F□
□□		5□ - 95□□□□□□□□
□□		□120□□□□□□□□□□