

# 2016 OCOM

## M / N OCBP-004A / B

- 200 Mhz 32 RISC 8 MB SDRAM
- 4 MB
- 127 Mm 5"
- 300 984' 25.4 Mm 1"
- Kiosk
- TSPL-EZ™ TPLE TPLZ

	OCBP-004A	OCBP-004B
Resolution	8 / mm 203DPI	12 / mm 300DPI
Resolution	&	
Resolution	127mm 5" / s	101.6mm 4" / s
Resolution	108 mm 4.25"	104 mm 4.09"
Resolution	2794 mm 110"	1016 mm 40"
Resolution	&	
Resolution	20-112mm 0.78"-4.4"	
Resolution	0.06 0.254 mm 2.36 10 mil	
Resolution	10 2,794mm 0.39" 110"	10 1,016 mm 0.39" 40"
Resolution	127 mm 5" &	
Resolution	300 m 67mm 1" 40mm 110mm 1.6" 4.3"	
Resolution	&	
Resolution	234mm W x 194.8mm H x 302.5mm D	
Resolution	3.1 6.83	
Resolution	32 RISC CPU	
Resolution	4MB	
Resolution	8MB SDRAM	
Resolution	SD 4 GB	
Resolution	•USB2.0•RS-232•Centronics•10/100 Mbps •802.11 b / g / n	
Resolution	&	
Resolution	AC 100-240V 1A 50-60Hz	
Resolution	DC 24V 2.5A 60W	
Resolution LED	1 & 1 LED 3 & blue	
Resolution	&	
Resolution	&	
Resolution	&	
Resolution	&	
Resolution	&	
Resolution	8 &	
Resolution	&	
Resolution	1D Code 39 Code 93 Code 128 UCC Code 128 A B C Codabar Interleaved 2 of 5 EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN UPC 2 5 MSI PLESSEY POSTNET 2D PDF-417 Maxicode DataMatrix QR	
Resolution	BIMAP BMP PCX 256	
Resolution	0° 90° 180° 270°	
Resolution	TSPL EPL ZPL DPL	

温度	5~40°C / 25~85°C
湿度	40~60% / 10~90%
认证	FCC / CE / CCC / CB
环保	RoHS
接口	①Windows CD; ②USB; ③USB; ④; ⑤; ⑥x 2, 1.5" x 2; ⑦x 2; ⑧; ⑨
传输	10 / 100Mbps / RS-232 / Centronics
尺寸	0.06~0.19mm 50000; 0.20~0.25mm / 20000
重量	25.4mm / 1" / 214mm / 8.4" 802.11 b / g / n / RFID

