

2016 OCOM

M / N OCBP-004A / B

-
- I 200 Mhz 32□RISC□□□□8 MB SDRAM□
- 4 MB□□
- I□□□□□□□□
- I 127 Mm□5“□□□□□□□□
- I 300□984“□□□□□□25.4 Mm□1“□□□□□
- I Kiosk□□□□□□□□
- I TSPL-EZ™ □□□□TPLE□TPLZ□□□□

□□□□	OCBP-004A	OCBP-004B
□□□	8□/ mm□203DPI□	12□/ mm□300DPI□
□□□□	□□□&□□□	
□□□□□□□	127mm□5“□/ s	101.6mm□4“□/ s
□□□□□□□	108 mm□4.25“□	104 mm□4.09“□
□□□□□□□	2794 mm□110“□	1016 mm□40“□
□□□□	□□□□□□□□□□□□□□□□□□□□	
□□□□	20-112mm□0.78“-4.4“□	
□□□□	0.06□0.254 mm□2.36□10 mil□	
□□□□	10□2,794 mm□0.39“□110“□	10□1,016 mm□0.39“□40“□
□□□□□	127 mm□5“□□□□□□□□□□	
□□□□□□□	300 m□□□□□□□□67mm□1“□□□□□□□□40mm□110mm□1.6“□4.3“□	
□□	□□□□	
□□□□	234mm□W□×194.8mm□H□×302.5mm□D□	
□□	3.1□□□6.83□□	
□□□	32□RISC CPU	
□□	4MB□□□□	
	8MB SDRAM	
	SD□□□□□□□□□□□□□□4 GB	
□□	•USB2.0•RS-232□□□□□□□□•Centronics□□□□□□□□•□□□□□□□□10/100 Mbps□□□□□□□□□□	
	•□□□□□□□□□□802.11 b / g / n□□□□□□□□□□	
□□	□□□□□□□□□□	
	□□□□□□100-240V□1A□50-60Hz	
	□□□□DC 24V□2.5A□60W	
□□□□□□□□LED	1□□□□□□□1□□□□□□& 1□LED□3□□□□□□□□□□& bule□	
□□□	□□□□□□□□□□□□□□□□	
	□□□□□□	
	□□□□□□□□□□	
	□□□□□□□	
□□□□	□□	
□□□□	8□□□□□□□□□□	
	□□TTF□□□□	
□□	1D□□□□Code 39□Code 93□Code 128UCC□Code 128□□A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□	
	EAN-128□UPC-A□UPC-E□EAN□UPC 2□5□□□□□□□□MSI□PLESSEY□POSTNET□	
	2D□□□□□PDF-417□Maxicode□DataMatrix□QR□	
□□	BIMAP□BMP□PCX□□□□256□□	
□□□□□□□□□	0°□90°□180°□270°	
□□□□□	TSPL□EPL□ZPL□DPL□	

温度	5~40°C / 25~85°C
湿度	40~60% / 10~90%
认证	FCC / CE / CCC / CB
环保	RoHS
接口	①Windows CD; ②USB; ③USB; ④; ⑤; ⑥x 2, 1.5" x 2; ⑦x 2; ⑧; ⑨
传输	10 / 100Mbps / RS-232 / Centronics
精度	0.06~0.19mm 50000; 0.20~0.25mm / 20000
尺寸	25.4mm / 1" / 214mm / 8.4" / 802.11 b / g / n / RFID

