

OCBP-004A / B
M / N OCBP-004A / B

200 Mhz 32 RISC 8 MB SDRAM
 4 MB Flash
 127 Mm 5
 300 984 25.4 Mm 1
 Kiosk
 TSPL-EZ™ TPLE TPLZ

Model	OCBP-004A	OCBP-004B
Resolution	8 / mm 203DPI	12 / mm 300DPI
Print Speed	&	
Print Width	127mm 5 / s	101.6mm 4 / s
Print Height	108 mm 4.25"	104 mm 4.09"
Print Length	2794 mm 110"	1016 mm 40"
Print Range		
Print Resolution	20-112mm 0.78"-4.4"	
Print Accuracy	0.06 0.254 mm 2.36 10 mil	
Print Area	10 2,794 mm 0.39" 110"	10 1,016 mm 0.39" 40"
Print Length	127 mm 5	
Print Width	300 m 67mm 1 40mm 110mm 1.6" 4.3"	
Dimensions		
Weight	234mm W x 194.8mm H x 302.5mm D	
Price	3.1 6.83	
Processor	32 RISC CPU	
Memory	4MB 8MB SDRAM SD 4 GB	
Connectivity	<ul style="list-style-type: none"> •USB2.0 •RS-232 •Centronics •10/100 Mbps •802.11 b / g / n 	
Power	100-240V 1A 50-60Hz DC 24V 2.5A 60W	
LED	1 LED 3 & blue	
Barcode	Code 39 Code 93 Code 128 UCC Code 128 A B C Codabar Interleaved 2 of 5 EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN UPC 2 5 MSI PLESSEY POSTNET 2D PDF-417 Maxicode DataMatrix QR	
Image	BIMAP BMP PCX 256	
Angle	0° 90° 180° 270°	
Language	TSPL EPL ZPL DPL	

温度	5~40°C/25~85°C -40~60°C/10~90°C
认证	FCC/CE/CCC/CB
环保	RoHS
接口	①Windows CD; ②USB; ③USB; ④; ⑤; ⑥x 2, 1.5" x 2; ⑦x 2; ⑧; ⑨
传输	10 / 100Mbps RS-232 Centronics
精度	0.06~0.19mm 50000; 0.20~0.25mm 20000
尺寸	25.4mm 1" 214mm 8.4" 802.11 b / g / n RFID

