

2016 OCOM
M / N OCBP-004A / B

200 Mhz 32 RISC 8 MB SDRAM
 4 MB
 127 Mm 5"
 300 984' 25.4 Mm 1"
 Kiosk
 TSPL-EZ™ TPLE TPLZ

Model	OCBP-004A	OCBP-004B
Resolution	8 / mm 203DPI	12 / mm 300DPI
Print Speed	mm/s	
Print Width	127mm 5"	101.6mm 4"
Print Height	108 mm 4.25"	104 mm 4.09"
Print Length	2794 mm 110"	1016 mm 40"
Print Thickness	mm	
Print Weight	20-112mm 0.78"-4.4"	
Print Density	0.06 0.254 mm 2.36 10 mil	
Print Area	10 2,794 mm 0.39" 110"	10 1,016 mm 0.39" 40"
Print Volume	127 mm 5"	
Print Capacity	300 m 67mm 1" 40mm 110mm 1.6" 4.3"	
Dimensions	mm	
Weight	234mm W x 194.8mm H x 302.5mm D	
Power	3.1 6.83	
Processor	32 RISC CPU	
Memory	4MB 8MB SDRAM SD 4 GB	
Connectivity	•USB2.0 •RS-232 •Centronics •10/100 Mbps •802.11 b / g / n	
Power Input	AC 100-240V 1A 50-60Hz DC 24V 2.5A 60W	
Lighting	LED 1 & 1 LED 3 & blue	
Barcode	Code 39 Code 93 Code 128 UCC Code 128 A B C Codabar Interleaved 2 of 5 EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN UPC 2 5 MSI PLESSEY POSTNET 2D PDF-417 Maxicode DataMatrix QR	
Image	BIMAP BMP PCX 256	
Orientation	0° 90° 180° 270°	
Compliance	TSPL EPL ZPL DPL	

温度	5~40°C / 25~85°C
湿度	40~60% / 10~90%
认证	FCC / CE / CCC / CB
环保	RoHS
接口	①Windows CD; ②USB; ③USB; ④; ⑤; ⑥x 2, 1.5" x 2; ⑦x 2; ⑧; ⑨
通信	10 / 100Mbps / RS-232 / Centronics
尺寸	0.06 x 0.19mm 50000; 0.20 x 0.25mm x 20000
重量	25.4mm x 1" x 214mm x 8.4" 802.11 b / g / n / RFID

