

2016 OCOM
M / N OCBP-004A / B

I 200 Mhz 32 RISC 8 MB SDRAM
 4 MB
 I 127 Mm 5"
 I 300 984' 25.4 Mm 1"
 I Kiosk
 I TSPL-EZ™ TPLE TPLZ

Model	OCBP-004A	OCBP-004B
Resolution	8 / mm 203DPI	12 / mm 300DPI
Print Speed	mm/s	
Print Width	127mm 5"	101.6mm 4"
Print Height	108 mm 4.25"	104 mm 4.09"
Print Length	2794 mm 110"	1016 mm 40"
Print Range	mm	
Print Resolution	20-112mm 0.78"-4.4"	
Print Weight	0.06 0.254 mm 2.36 10 mil	
Print Volume	10 2,794mm 0.39" 110"	10 1,016 mm 0.39" 40"
Print Length	127 mm 5"	
Print Width	300 mm 67mm 1" 40mm 110mm 1.6" 4.3"	
Weight	mm	
Dimensions	234mm W x 194.8mm H x 302.5mm D	
Price	3.1 6.83	
CPU	32 RISC CPU	
Memory	4MB 8MB SDRAM SD 4 GB	
Connectivity	<ul style="list-style-type: none"> •USB2.0 •RS-232 •Centronics •10/100 Mbps •802.11 b / g / n 	
Power	AC 100-240V 1A 50-60Hz DC 24V 2.5A 60W	
LED	1 LED & 1 LED 3 & blue	
Barcode	Code 39 Code 93 Code 128 UCC Code 128 A B C Codabar Interleaved 2 of 5 EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN UPC 2 5 MSI PLESSEY POSTNET 2D PDF-417 Maxicode DataMatrix QR	
Image	BIMAP BMP PCX 256	
Angle	0° 90° 180° 270°	
Language	TSPL EPL ZPL DPL	

温度	5~40°C / 25~85°C
湿度	40~60% / 10~90%
认证	FCC / CE / CCC / CB
环保	RoHS
接口	①Windows CD; ②USB; ③USB; ④; ⑤; ⑥x 2, 1.5" x 2; ⑦x 2; ⑧; ⑨
传输	10 / 100Mbps / RS-232 / Centronics
精度	0.06~0.19mm 50000; 0.20~0.25mm / 20000
尺寸	25.4mm / 1" / 214mm / 8.4" / 802.11 b / g / n / RFID

