

OCBP-004--2016 OCOM



M / N OCBP-004A / B

- 200 Mhz 32 RISC 8 MB SDRAM
- 4 MB
- 127 Mm 5
- 300 984 25.4 Mm 1
- Kiosk
- TSPL-EZ TPLE TPLZ

OCBP-004A	OCBP-004B
8 / mm 203DPI	12 / mm 300DPI
127mm 5 / s	101.6mm 4 / s
108 mm 4.25	104 mm 4.09
2794 mm 110	1016 mm 40
20-112mm 0.78-4.4	
0.06 0.254 mm 2.36 10 mil	
10 2,794 mm 0.39 110	10 1,016 mm 0.39 40
127 mm 5	
300 m 67mm 1 40mm 110mm 1.6 4.3	
234mm W x 194.8mm H x 302.5mm D	
3.1 6.83	
32 RISC CPU	
4MB	
8MB SDRAM	
SD 4 GB	
<ul style="list-style-type: none"> •USB2.0•RS-232•Centronics•10/100 Mbps •802.11 b / g / n 	
AC 100-240V 1A 50-60Hz	
DC 24V 2.5A 60W	
LED	1 LED 3 & blue
8	
TTF	
1D Code 39 Code 93 Code 128 UCC Code 128 A B C Codabar Interleaved 2 of 5 EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN UPC 2 5 MSI PLESSEY POSTNET 2D PDF-417 Maxicode DataMatrix QR	
BIMAP BMP PCX 256	
0 90 180 270	
TSPL EPL ZPL DPL	

温度	5~40°C / 25~85°C
湿度	40~60% / 10~90%
认证	FCC / CE / CCC / CB
环保	RoHS
接口	①Windows CD; ②USB; ③USB; ④; ⑤; ⑥x 2, 1.5" x 2; ⑦x 2; ⑧; ⑨
传输	10 / 100Mbps / RS-232 / Centronics
精度	0.06 / 0.19mm 50000; 0.20 / 0.25mm / 20000
尺寸	25.4mm / 1" / 214mm / 8.4" 802.11 b / g / n / RFID

