

TransferBarCode
M / N OCBP-004A / B

L 200 MHz32RISC8 MB SDRAM
4 MB
L-
1275"
300984'25.41"
L
TSPL-EZ™TPLETPLZ

	OCBP-004A	OCBP-004B
	8/ mm203 dpi	12/ mm300 DPI
	1275"/ s	101.64"/ s
	1084.25"	1044.09"
	2794110"	101640"
	20-112mm0.78"-4.4"	
	0.060.2542.3610	
	1027940.39"110"	1010160.39"40"
	1275"OD	
&:	300m OD671"401101.6"4.3"	
	234Wx194.8x302.5D	
	3.16.83	
	32RISC CPU	
	4MBMenmemory	
	8MB SDRAM	
	SDFlash4 GB	
	•USB2.0•RS-232•10/100 Mbps •Bluethooth•802.11 b / g / n	
	AC 100-240V1A50-60Hz	
	DC 24V2.5A60W	
LED	11LED; BULE	
	8	
	TTF	
	3993128UCC128AB5 2EAN-8EAN-13 EAN-128UPC-AUPC-EANUPC 25PLESSEYPOSTNET PDF-417MAXICODEDataMatrixQR	
	BIMAPBMPPCX256	
	0°90°180°270°	
	TSPLZEPLZPLDPL	
	540°C2585	
	-4060°C1090	

認證	FCCCECCC
認證	RoHS
配件	①WindowsCD;②Quick;③USB;④Power; ⑤External;⑥Label×21.5"×2; ⑦Ribbon×2;⑧Ribbon;⑨Media
通訊	10/100 MbpsRS-232Centronics
尺寸	0.060.19 500000; 0.200.25mm20
重量	OD 2148.4"25.4"1" 802.11 b / g / nRFIDmodule

