

2016

M / N OCBP-004A / B

L 200 MHz 32 RISC 8 MB SDRAM  
 4 MB  
 L-  
 127 5"  
 300 984' 25.4 1"  
 L  
 TSPL-EZ™ TPLE TPLZ

|                | OCBP-004A   | OCBP-004B         |
|----------------|---|-------------------|
| Resolution     | 8 / mm 203 dpi  | 12 / mm 300 DPI   |
| Resolution     | Resolution; dpi   |                   |
| Resolution     | 127 5" / s  | 101.6 4" / s      |
| Resolution     | 108 4.25"   | 104 4.09"         |
| Resolution     | 2794 110"   | 1016 40"          |
| Resolution     | Resolution  |                   |
| Resolution     | 20-112mm 0.78"-4.4"   |                   |
| Resolution     | 0.06 0.254 2.36 10  |                   |
| Resolution     | 10 2794 0.39" 110"  | 10 1016 0.39" 40" |
| Resolution     | 127 5" OD   |                   |
| Resolution     | 300m OD67 1" 40 110 1.6" 4.3"   |                   |
| Resolution     | Resolution  |                   |
| Resolution     | 234 W x 194.8 x 302.5 D   |                   |
| Resolution     | 3.1 6.83  |                   |
| Resolution     | 32 RISC CPU   |                   |
| Resolution     | 4MB Memory  |                   |
| Resolution     | 8MB SDRAM   |                   |
| Resolution     | SD Flash 4 GB   |                   |
| Resolution     | <ul style="list-style-type: none"> <li>• USB 2.0 • RS-232 • • • 10/100 Mbps</li> <li>• Bluetooth • 802.11 b / g / n</li> </ul>                      |                   |
| Resolution     | Resolution  |                   |
| Resolution     | AC 100-240V 1A 50-60Hz  |                   |
| Resolution     | DC 24V 2.5A 60W   |                   |
| Resolution LED | 1 LED; 1 LED; BULE  |                   |
| Resolution     | Resolution  |                   |
| Resolution     | Resolution  |                   |
| Resolution     | Resolution  |                   |
| Resolution     | Resolution  |                   |
| Resolution     | Resolution  |                   |
| Resolution     | 8 Resolution  |                   |
| Resolution     | Resolution  |                   |
| Resolution     | Resolution 39 93 128 UCC 128 A B C 5 2 EAN-8 EAN-13<br>EAN-128 UPC-A UPC-E EAN UPC 2 5 PLESSEY POSTNET<br>Resolution PDF-417 MAXICODE DataMatrix QR |                   |
| Resolution     | BIMAP BMP PCX 256   |                   |
| Resolution     | 0° 90° 180° 270°  |                   |
| Resolution     | TSPL EPL ZPL DPL  |                   |
| Resolution     | Resolution 5 40°C 25 85   |                   |
| Resolution     | Resolution -40 60°C 10 90   |                   |

|        |  |
|--------|--|
| □□□□   | FCC□CE□CCC□CB  |
| □□□□   | □□RoHS   |
| □□     | ①Windows□□□□CD□;②Quick□□□□;③USB□□;④Power□;<br>⑤External□□□□□□;⑥Label□□□□□□×2□1.5"□□□□□□×2;<br>⑦Ribbon□□×2;⑧Ribbon□□;⑨Media |
| □□□□   | □□□□□10/100 Mbps□□RS-232□Centronics□□□□  |
| □□□□□□ | □□□□□□□□□□□□□□□□0.06□0.19□□□<br>500000□□; 0.20□□0.25mm□20□□□   |
| □□□□   | □□□□□□□OD□ 214□□□8.4"□□25.4□□1"□□□□□□□□□□□□<br>□□□□□□□□□□□□802.11 b / g / n□□□□□□□□□□□□RFIDmodule□                         |

