

TransferBarCode

M / N OCBP-004A / B

L 200 MHz 32 RISC 8 MB SDRAM  
 4 MB  
 L-  
 127 5"  
 300 984' 25.4 1"  
 L  
 TSPL-EZ™ TPLE TPLZ

	OCBP-004A	OCBP-004B
	8 / mm 203 dpi	12 / mm 300 DPI
	127 5" / s	101.6 4" / s
	108 4.25"	104 4.09"
	2794 110"	1016 40"
	20-112mm 0.78"-4.4"	
	0.06 0.254 2.36 10	
	10 2794 0.39" 110"	10 1016 0.39" 40"
	127 5" OD	
	300m OD67 1" 40 110 1.6" 4.3"	
	234 W x 194.8 x 302.5 D	
	3.1 6.83	
	32 RISC CPU	
	4MB Memory	
	8MB SDRAM	
	SD Flash 4 GB	
	•USB2.0 •RS-232 • • 10/100 Mbps •Bluetooth • 802.11 b / g / n	
	AC 100-240V 1A 50-60Hz	
	DC 24V 2.5A 60W	
	LED	
	8	
	TTF	
	39 93 128UCC 128 A B C 5 2 EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN UPC 2 5 PLESSEY POSTNET PDF-417 MAXICODE DataMatrix QR	
	BIMAP BMP PCX 256	
	0° 90° 180° 270°	
	TSPL EPL ZPL DPL	
	5 40°C 25 85 -40 60°C 10 90	

□□□□	FCC□CE□CCC□CB
□□□□	□□RoHS
□□	①Windows□□□□CD□;②Quick□□□□;③USB□□;④Power□; ⑤External□□□□□□;⑥Label□□□□□□×2□1.5"□□□□□□×2; ⑦Ribbon□□×2;⑧Ribbon□□;⑨Media
□□□□	□□□□□10/100 Mbps□□RS-232□Centronics□□□□
□□□□□□	□□□□□□□□□□□□□□□□0.06□0.19□□□ 500000□□; 0.20□□0.25mm□20□□□
□□□□	□□□□□□□OD□ 214□□□8.4"□□25.4□□1"□□□□□□□□□□□□ □□□□□□□□□□□□802.11 b / g / n□□□□□□□□□□□□RFIDmodule□

