

TransferBarCode
M / N OCBP-004A / B

L 200 MHz 32 RISC 8 MB SDRAM
 4 MB
 L-
 127 5"
 300 984' 25.4 1"
 L
 TSPL-EZ™ TPLE TPLZ

OCBP-004A	OCBP-004B
8 / mm 203 dpi	12 / mm 300 DPI
127 5" / s	101.6 4" / s
108 4.25"	104 4.09"
2794 110"	1016 40"
20-112mm 0.78"-4.4"	
0.06 0.254 2.36 10	
10 2794 0.39" 110"	10 1016 0.39" 40"
127 5" OD	
300m OD67 1" 40 110 1.6" 4.3"	
234 W x 194.8 x 302.5 D	
3.1 6.83	
32 RISC CPU	
4MB Memory	
8MB SDRAM	
SD Flash 4 GB	
•USB2.0 •RS-232 •10/100 Mbps •Bluetooth •802.11 b / g / n	
AC 100-240V 1A 50-60Hz	
DC 24V 2.5A 60W	
1 LED; BULE	
8	
TTF	
39 93 128UCC 128A B C 5 2 EAN-8 EAN-13 EAN-128 UPC-A UPC-E EAN UPC 2 5 PLESSEY POSTNET PDF-417 MAXICODE DataMatrix QR	
BIMAP BMP PCX 256	
0° 90° 180° 270°	
TSPL EPL ZPL DPL	
5 40°C 25 85 -40 60°C 10 90	

CCC	FCC CE CCC CB
RoHS	RoHS
Accessories	① Windows CD; ② Quick Start; ③ USB; ④ Power; ⑤ External; ⑥ Label 2x1.5"; ⑦ Ribbon x2; ⑧ Ribbon; ⑨ Media
Ports	10/100 Mbps RS-232 Centronics
Dimensions	0.06x0.19 500000; 0.20x0.25mm 20
Weight	OD 214x8.4"x25.4"x1" 802.11 b / g / n RFID module

